

Xtreme-Light[®]



Features

Xtreme-Light[®] fiber designed for rugged applications uses, with a unique high modulus coating for better survivability in harsh environments. Xtreme-Light[®] cable designs are compression resistant constructions, hydrostatic tested to 15kpsi, subsea depths to 10km. Xtreme-Light[®] cables are available as sub-cables in composite electro-optical cables on other Falmat ROV tethers and "Xtreme-Marine[®] EO".

Simplex Designs

Flexible fiber tether with high modulus coated fiber, synthetic strength member and Xtreme-grade polyurethane jacket.

Multi-fiber Designs

Compact designs with semi-rigid center strength core, waterblocked interstice and "Xtreme" grade polyurethane jacket.

Optional Ordering

- Increased Strength
- Neutral Buoyant
- Bend Insensitive Fibers
- Optional Colors

Fiber Properties	Fiber Type:	Single Mode	Multimode	Multimode
	Diameters:	9.3/245/900um	62.5/125/245/900um	50/125/245/900um
IEC/ISO 11801	OS2	OM1	OM4	
TIS/EIA	492AAA	494AAAA	494AAAD	
Attenuation db/km:	@ 1310/ .40 @ 1550/ .30	@ 850db/ 3.5 @ 1300db/ 1.0	@ 850db/ 3.0 @ 1300db/ 1.0	
Proof Test:	200 kpsi	200 kpsi	200 kpsi	
Temp Range				
900um Fiber:	-60c to 150c	-60c to 150c	-60c to 150c	
Xtreme PU Jacketed:	-60c to 120c Short term -60c to 90c Long Term	-60c to 120c Short term -60c to 90c Long Term	-60c to 120c Short term -60c to 90c Long Term	

PART NUMBER	TYPE/POWER	BREAK STRENGTH		FINISHED DIAMETER		MIN BEND RADIUS		WEIGHT AIR	
		LBS.	KG	INCH	MM	INCH	MM	LB/1000FT	KG/KM
SIMPLEX									
FM011402SM12	Single Mode	300	136	0.092	2.3	2.0	50	3.5	5.2
FM011402SM13	Single Mode	300	136	0.118	3.0	2.0	50	5.7	8.5
FM011402MM12	MM 62.5/125	300	136	0.092	2.3	2.0	50	3.5	5.2
FM011402MM13	MM 62.5/125	300	136	0.118	3.0	2.0	50	5.7	8.5
SIMPLEX NEUTRAL BUOYANT									
FM011402SMNBT	Single Mode	300	136	0.144	3.7	2.0	50	7.3	10.9
FM011402MMNBT	MM 62.5/125	300	136	0.144	3.7	2.0	50	7.3	10.9
FM011402SMNBF*	Single Mode	300	136	0.100	2.5	2.0	50	3.5	5.2
FM011402MMNBF*	MM 62.5/125	300	136	0.100	2.5	2.0	50	3.5	5.2
MULTIFIBER									
FM091003-1402	3 ea.	200	90	0.180	4.6	3.0	76	14	21
FM091003-1403	4 ea.	200	90	0.180	4.6	3.0	76	14	21
FM091003-1404	6 ea.	200	90	0.180	4.6	3.0	76	15	22
FM091003-1406	3 ea.	200	90	0.180	4.6	3.0	76	14	21
FM091003-1408	4 ea.	200	90	0.180	4.6	3.0	76	14	21
FM091003-1412	6 ea.	200	90	0.180	4.6	3.0	76	15	22

* Foam Polyurethane Jacket designs rated to 150m depth.

Composite electro-optic cables with Xtreme-Light[®] available, see "Xtreme-Green[®] Fiber" and "Xtreme-Marine[™] EO" data sheets.



Falmat, Inc.
1873 Diamond Street
San Marcos, CA 92078 USA

760.471.5400 Tel/
760.471.4970 Fax
www.falmat.com

©2016 Falmat Inc. All rights reserved. Made in the USA.

Rev. 2.9.17